

STL Alloy Wheel Blaster



For fast preparation of alloy wheels

Safe & economical

Preps a wheel in just minutes!

STL Alloy Wheel Blaster

Complete with the following:

- Internal tilt bed table complete with center mounting for alloy wheels up to 22" diameter
- Spacious cabinet
- High flow suction-fed system
- Fully controllable with foot pedal operation
- Pressure regulator & gauge mounted on front of machine
- High-performance dust collection
- Halogen lighting for excellent internal visibility
- Full front gas assisted opening door
- Air-wash gun
- Single phase or 3-phase electrics (customer's choice at no additional cost)
- In-line water trap
- Twin Cartridge auto-clean extractor

Capacity: 0.33m³

Maximum Airflow: 18cfm

Air Pressure: 60-100psi

Air Inlet Size: 1/4" BSP

Overall Height: 1500mm

Overall Width: 960mm

Depth: 720mm

Doors: 2

Extraction Port Ø: 64mm

Viewing Area: 580 x 270mm

On site Services required

Electric: 16A single-phase power supply (optional 3-phase unit)

Compressed air: 80-100psi / 12-16cfm

Routine Maintenance

Regular service is important to keep your machine in working order and ensure safe, reliable and trouble free operation. Talk to STL about our comprehensive Service Care Plan.